

RD BAR

	C6 Alloy Rd. Bar		0.027	20.75	11.875	2	3.8
X	4130 cond-c4	MIL-S-6758	0.312	0.312	48	1	1.3
X	4130 sq bar HT-F4	MIL-S-6758	0.312	0.312	36.75	3	3.1
	4130 Sq. bar	Cold Finished ASTM-A-331-87	0.37	0.37	71.875	1	2.8
	4130 Sq. Bar	Cond-A	1.5	1.5	117	1	75.3
X	4130 Rect bar	AMS-6438	2	2.5	8	1	11.4
X	4130 Rect bar	Cond-E4	2.5	3.75	48	1	128.7
X	4130 Rect Radius Edge	AMS-6438	2.25	4.25	25.25	1	69.1
X	4130 Rect Radius Edge	Norm AMS-6438	2.25	4	37.5	3	289.6
X	4130 Rect Radius Edge	Norm AMS-6438	2.25	4	51	1	131.3
X	4130 Rd. Bar	MIL-S-6758	0.25		23.75	12	4.5
	4130 Rd. Bar	MIL-S-6758	0.25		24	4	1.5
	4130 Rd. Bar	MIL-S-6758 Cond-N	0.25		11.875	1	0.2
X	4130 Rd Bar	MIL-S-6758	0.312		144	4	14.3
	4130 Rd. Bar		0.312		11	1	0.3
X	4130 RD BAR	AMS-6758 COND-F-4	0.438		66.875	1	2.8
	4130 Rd. Bar	MIL-S-6758 Cond-N	0.5		23.75" & 36	2	0.0
	4130 Rd. Bar		0.5		48	2	6.1
X	4130 Rd. Bar	MIL-S-6758B	0.5		45	1	2.9
	4130 Rd. Bar		0.625		12	1	1.2
	4130 Rd. Bar	MIL-T-6758	0.625		4.125	1	0.4
	4130 Rd. Bar		0.625		10.875	1	1.1
	4130 Rd. Bar	MIL-S-6758B	0.625		12	1	1.2
	4130 Rd. Bar	MIL-S-6758B	0.75		5.875	1	0.8
	4130 Rd. Bar	MIL-S-6758B	0.75		47.5	1	6.8
	4130 Rd. Bar	MIL-S-6758B	0.875		25	3	14.7
	4130 Rd Bar	MIL-S-6758B	0.875		95.75	1	18.7
	4130 Rd. Bar	MIL-S-6758B	0.875		144.5	1	28.2
	4130 Rd. Bar	MIL-S-6758B	0.875		48	1	9.4
X	4130 Rd. Bar	AMS-2301J cond F4	1.25		48	1	19.1

X	4130 Rd. Bar	AMS-2301J cond F4	1.25		39	1	15.5
X	4130 Rd. Bar	AMS-2301J cond F4	1.25		47	1	18.7
	4130 Rd. Bar	MIL-S-6758B Cond C4	1.5		24	1	13.8
X	4130 Rd. Bar	MIL-S-6758B	1.5		144	6	496.1
	4130 Rd. Bar	MIL-S-6758B	1.625		7.75	1	5.2
	4130 Rd. Bar	MIL-T-6758	1.75		24.25	1	19.0
X	4130 Rd. Bar		2		16.5	1	16.8
X	4130 RD BAR	MIL-T-6758	2.125		44.875	1	45.7
	4130 Rd. Bar	AMS-6370, Cond-N	7		37.5	1	468.9
X	4130 RD BAR	AMS-6409	7.25		6.9375	1	83.1
X	4130 RD BAR		7.25		14.5	1	172.2
X	4130 Rd. Bar	MIL-S-6758B	8		5.5	1	89.8
X	4130 Steel		25.5		9.5	2	3152.6
X	4135 RD BAR	HRRD	1.25		11.875	1	4.2
X	4130 Flar Bar	ASTM-A-331-95	0.25	4	48	1	13.7
	4130 Flat Bar	AMS-6758	0.25	2	72	3	30.9
	4130 Flat Bar	AMS-6758	0.25	4	70.75	2	40.5
X	4130 Flat Bar	AMS-6758	0.5	0.5	84	1	6.0
X	4130 Flat Bar	AMS-6758	0.5	2	60	1	17.2
	4130 Flat Bar	AMS-6758	0.5	0.75	71	1	7.6
	4130 Flat Bar	AMS-6758	0.25	3	23	3	14.8
	4130 Flat Bar	AMS-6758	0.25	4.125	72.125	3	63.8
	4130 Flat Bar	MIL-S-6758	0.625	1.25	19.75	1	4.4
X	4130 Flat Bar	AMS-6758	0.75	6	153.675	1	197.8
X	4130 Flat Bar	AMS-6758	0.75	6	85.25	1	109.7
X	4130 Flat Bar	AMS-6758	1	2.5	27.9375	1	20.0
	4130 Rect. Bar	AMS-6758	1.3	1.5	84	1	46.8
X	4130 Flat Bar	AMS-6758	1.4375	2.5	24	1	24.7

X	4130 Flat Bar	AMS-6758	1.5	2.5	147.75	1	158.5
X	4130 Flat Bar	AMS-6758	1.5	2.5	36	1	38.6
X	4130 Rect. Bar	AMS-6758	1.5	2.5	120	1	128.7
	4130 Rect. Bar	AMS56758	1.5	2.125	24.25	1	22.1
	4130 Rect. Bar	ASTM-A331-95, ASTM-A108-03	1.5	2	13.5	1	11.6
X	4130 Flat Bar Cond-N	AMS-6758	1.5	2.5	24	1	25.7
	4130 Flat Bar	AMS-6758	1.5	5	17	1	36.5
X	4130 Flat Bar machine	MIL-S-6758	1.75	2.5	72	1	90.0
	4130 Flat Bar (CF)	MIL-S-6758	2	5	6.625	1	18.9
X	4130 Flat Bar	AMS-6758	2.375	4.25	15.875	1	45.8
X	4130 bar	AMS-6348	6.25	5.5	1	54.8	
X	4140 Rd. Bar	MIL-S-24093A CL-C TY-2	3	36	3	219.6	
	4140 Rd. Bar	MIL-S-24093A CL-C TY-2	3.25	27.75	1	66.2	
X	4140 Rd bar	AMS-6382	0.625	144	1	14.4	
X	4140 Rd bar	AMS-6382	0.625	84	1	8.4	
X	4140 Rd. Bar	AMS-6349	0.875	24	1	4.7	
	4140 Rd. Bar	AMS-6349	0.875	76	2	29.7	
X	4140 Rd. Bar	AMS-6349	1.5	105	1	60.3	
	4140 Rd. Bar	MIL-S-5626	1.25	11.75	2	9.4	
	4140 Rd. Bar	Norm AMS-6349	3.25	11.75	1	31.7	
	4140 Rd. Bar	Norm AMS-6349	3.25	14.375	1	38.7	
	4140 Rd. Bar	Norm AMS-6349	3.25	52.25	1	140.8	
	4140 Rd. Bar	Norm AMS-6349	3.25	22.375	1	60.3	
	4140 Rd. Bar	Norm AMS-6349	3.25	12.125	1	32.7	
	4140 Rd. Bar	Norm AMS-6349	3.25	12.875	1	34.7	
	4140 Rd. Bar	Norm AMS-6349	3.25	37.375	1	100.7	
X	4140 Rd Bar	AMS-6382	4	13.25	1	47.8	
	4140 Rd. Bar	ASTM-A331	4	7.875	1	32.2	
X	4140 Rd. Bar	AMS-6349	5.5	11	15	1273.6	

X	4140 Rd. Bar	AMS-6382	7.5		72	1	1033.4
X	4140 Flat Bar	MIL-S-5626C, Cond-C4, AMS-S-5626	0.25	1	88.5	2	12.7
	4140 Flat Bar		0.25	1	24	1	1.7
X	4140 Flat Bar Norm.& Temper to HRC 35-40	AMS-6382	0.75	2	53	1	22.7
X	4140 Rect bar	AMS-6382	1.875	2.625	147	1	206.9
X	4140 Rect bar	AMS-6382	1.875	2.5	151	1	202.4
X	4140 Rect bar Cond 150 KSI		2	6	12"& 24"	2	123.5
X	4140 Rect bar	AMS-6382	2	2.75	150.75	1	237.1
X	4140 Rect bar	AMS-6382	2	3	9.5	1	16.3
X	4140 Rect bar	AMS-6382	2	4	12	1	27.4
X	4140 Rect bar	AMS-6382	2.25	2.5	151.25	1	243.3
X	4140 Rect bar	AMS-6382	2.375	2.69	19	1	34.7
X	4140 Rect bar	AMS-6382	2.5	4	12	1	34.3
X	4140 Rect bar	AMS-6382	3.25	3.75	6.75	1	23.5
X	4340 Rd. Bar	AMS-6414, Electric Var	1.25		285.5	3	341.5
X	4340 Rd. Bar	Cold Finsihed, Cond-E-3, AMS-6415P	2		24.5	1	25.0
X	4340 Rd. Bar	Cold Finished, Cond E-3, AMS-6415R, AMS-S-5000	2		22	1	22.5
X	4340 Core	AMS-6409, Electric-VDG	2.875		32.25	1	68.0
X	4340 Rd. Bar	MIL-S-5000E, Cond F	3		7.875	1	18.1
	4340 Rd. Bar	MIL-S-5000	4		10.5	1	42.9
X	4340 Rd Bar	CL-B TY-1 MIL-S-24093A	4		8.25	1	33.7
X	4340 RD BAR	CL-B TY-1 MIL-S-24093A	4		8.25	1	29.8
	4340 Rd. Bar	AMS-6415, AMS-2301, MIL-S-5000 Cond-E1	5.25		8.5" 7" 9.75" 11.75"	5PCS	
X	4340 Rd. Bar	AMS-6415, AMS-2301, MIL-S-5000 Cond-E1	5.5		109	1	841.4
X	4340 Rd. Bar	MIL-S-5000	8		1.375	1	22.5
X	4340 Rd. Bar	MIL-S-5000, Cond E3	11		2	1	61.8
X	4340 Rd. Bar	AMS-S-5000, AMS-6484, AMS-6415	12		1.625	1	59.7

X	4340 Hex. Bar	AMS-64155	0.5		24.125	4	6.2
	4340 Hex. Bar	AMS-64155	0.625		49	1	4.9
	4340 Rect. Bar	MIL-S-5000	1	1.5	4.625	1	2.0
X	4340 Rect. Bar	MIL-S-5000	1.25	2	17.5	1	12.5
X	4340 Rect. Bar	MIL-S-5000	1.5	2.5	31	1	33.2
X	4340 Rect. Bar	MIL-S-5000	1.5	1.5	19	2	24.5
X	4340 SQ BAR		2	2	14.75	1	16.9
X	4340 Rect Bar Cond. C	MIL-S-5000	2.25	2.75	8.5	1	15.0
X	4340 Rect Bar	ASTM-A322	3	6	23	1	118.4
X	4340 Rect Bar	ASTM-A322	3	6	96.5	1	496.8
X	4340 Sq Bar	ASTM-A322	4	4	10.5	1	48.0
	8620 Rd. Bar	G86200-212 Rev 7	0.5		155.25	2	19.8
X	8620 RD BAR	ASTM-A108-07 ASTM-A331-95	1"		130.5	1	29.4
	8620 Rd. Bar	ASTM-A331	3.75		9.25	1	33.2
	8640 Rd. Bar		2.5		108	17	2928.1
	9310 Rd.Bar	ASTM-A-535	4.5		6.5	1	33.6
	Nitriding Rd. Bar	AMS-6470	1.25		47.375	1	18.9
	Nitriding Rd. Bar	AMS-6471	2.25		36	2	93.0
X	Alloy 42	ASTM-F-30	0.125	7.625	10.125	1	2.7
X	Alloy 42	ASTM-F-30	0.375	11	12	1	14.1

X	ALLOY 50 Pyrowear	RCS-BLT / AMS-6308D	0.375	8	8	1	6.8
X	ALLOY 50 Pyrowear	RCS-BLT / AMS-6308D	0.5	8	8	1	9.1