

# BAR

C101 Rd. Bar	ASTM-B-187	0.125		144.5	6	3.2
C101 Rd. Bar	ASTM-B-187	0.375		17	2	1.1
C101 Rd. Bar	ASTM-B-187	0.5		45.5	1	2.7
X C10100 Rd Bar	ASTM-B-187	0.75		26	1	3
<hr/>						
C101 Sq. Bar		0.625	0.75	30.75	1	2.8
<hr/>						
C10200 Rd. Bar		0.25		59	2	1.7
C10200 Rd. Bar		0.625		24.125	1	2.2
C10200 Rd. Bar		0.625		11.125	1	1.0
<hr/>						
C110 Rd. Bar		0.5		35.5	2	4.2
C110 Rd. Bar	Cond-Hard ASTM-B-187	0.75		119.75	1	15.9
<hr/>						
C110 Flat Bar		0.5	5.625	5.625	1	0.3
<hr/>						
C110 Sq. Bar		0.625	0.625	23.5	1	2.2
C110 Sq. Bar		0.625	0.625	72	1	6.6
C110 Sq. Bar	ASTM-B-187	0.625	0.625	71.75	1	6.6
C110 Sq. Bar		0.625	0.625	23.625	1	2.2
C110 Sq. Bar		1	1	3.5	1	0.8
<hr/>						
C122 Rect. Bar	ASTM-B577 ASTM-B152	0.5	0.75	48	2	5.7
<hr/>						
C145 Rd. Bar		0.125		72	2	0.5
C145 Rd. Bar	ASTM-B-301	0.5		72	2	8.5

	C172 Rd. Bar		0.125	26.75	3	0.3
	C172 Rd. Bar		0.125	23.625	5	0.4
	Be Cu 172 Rd. Bar	ASTM-B196-98A	0.136	143.75	30	18.8
	C172 Rd. Bar	QQC-530C-B196	0.75	11.875	1	1.6
	C172 Rd. Bar	AMS-4651A	1	56	5	65.9
	C172 Rd. Bar	AMS-4651A	1	48.75	1	11.5
X	C172 Rd. Bar	AMS-4651A	1	45.25	7	74.6
	C172 Rd. Bar	AMS-4651A	1	47	4	44.3
	C172 Rd. Bar	AMS-4651A	1	48.5	5	57.1
X	C17300-TD04	ASTM-B-196-03	0.25	72	1	1.1
X	C17500 TD04, hard		0.625	18.875	1	1.7
X	C17500 TD04, hard		0.625	16.875	1	1.6
	C16400 Rd. Bar	1/2 Hard	0.375	144.25	1	4.8
	C260 Rd. Bar		0.185	12	4	0.4
	C276 Rd. Bar		0.185	145.375	1	1.2
	3360 Beryl-Nickel Rd. Bar	T-B00	0.5	72.25	2	8.5
	C36000 Sq. Bar	1/2 Hard	0.25	33	1	0.5
	360 Hex. Bar		0.188	23	1	0.2
	360 Hex. Bar		0.312	47.25	1	1.1
	360 Hex. Bar	ASTM-B16	0.5	143	1	8.4

	360 Hex. Bar		0.75		47.75	1	6.3
	360 Hex. Bar	Cold Drawn H/H	1.25		31.375	1	11.5
	360 Flat Bar	ASTM-B-16-92 HO2	0.25	1	38	1	0.6
	360 Flat Bar	Cold Finished	0.25	1.5	72	2	2.1
	360 Flat Bar	1/2 Hard	0.25	1	66.25	1	1.0
X	360 Flat Bar	1/2 Hard, ASTM-B-16	0.375	4	17.5	1	8.0
	360 Flat Bar		0.5	0.75	11.75	1	0.7
	360 Flat Bar	MIL-I-45208A	0.5	1.5	12	1	0.7
X	360 Flat Bar	, ASTM-B-16	0.5	1.5	24	1	1.4
X	360 sq bar	ASTM-B-16	0.5	0.5	29.5	1	1.7
	360 Flat Bar	1/2 Hard, ASTM-B-16	2	3	6.75	1	6.4
X	360 sq bar	ASTM-B-16	0.625	0.625	29.75	1	2.7
	360 Rd. Bar		0.125		59.875	1	0.2
	360 Rd. Bar	CDA ASTM-B-16 & 249	0.25		132	1	1.0
	360 Rd. Bar	1/2 Hard, ASTM B16 & 249	0.25		144.5	4	8.5
	360 Rd. Bar	H/H ASTM-B16	0.625		120.5	1	11.1
X	360 Rd. Bar	CF ASTM-B16	0.75		70.5	1	9.3
	360 H/H Rd. Bar		1.125		23.625	1	7.0
	360 H/H Rd. Bar	ASTM-B16	1.625		69	1	42.9
	360 Rd. Bar	Alum. Brnz.	4.25		5	1	21.3
X	360 hex bar	ASTM-B16	0.5625		11.5	1	0.9
	360 RD BAR	ASTM-B16	1.5		38.5	1	
X	464 Naval Brass Rd. Bar	1/2 Hard, ASTM-B21 H02	0.1875		144	4	4.8
X	464 Naval Brass Rd. Bar	ASTM-B21 H02	0.5		8	1	0.5
X	C46400 Naval Brass Temper HRO2	ASTM-B -21-06	0.5		87.5	1	5.3
	464 Naval Brass Rd. Bar		0.625		72.875	1	6.7
	464 Naval Brass Rd. Bar	ASTM-B21 H02	0.75		42.5	1	5.6

X	464 Naval Brass Rd. Bar	ASTM-B21 H02	0.75	11.875	4	6.3
	464 Naval Brass Rd. Bar		1.375	15.875	1	7.1
	464 Naval Brass Rd. Bar	ASTM-B21 H02	6.75	2.25	1	24.1
X	C46400 cold drawn	ASTM-B21-06	1"DIA	11.75 &	7.625	2
	464 NAVAL BRASS RD BAR		1	20	1	
X	C510 hex Bar	ASTM-B-139	0.375	24.187	1	0.8
X	C510 hex Bar	ASTM-B-139	0.375	72.5	1	2.4
X	C510 Rd. Bar	HARD ASTM-B-139	0.625	72	1	6.6
	C510 Rd. Bar	QQB750/Cond Hard	0.75	11.75	1	1.6
	C510 Rd. Bar	QQB750/Cond Hard	0.75	72	1	9.5
	C510 hex Bar	ASTM-B-139	1.125	47	1	14.0
	52100 Rd. Bar	AMS-6440	2	72	2	135.6
X	C544 Rd. Bar	ASTM-B139-95/ QQB-750 H04 HARD ALLOY B	0.5	77.75	1	4.6
	C544 Rd. Bar	ASTM-B139-95/ QQB-750 H04 HARD ALLOY B	1	23.5	1	5.5
	623 Rd. Bar	ASTM-B150, AMS-4635D	0.875	35.875	1	6.5
	623 Rd. Bar	ASTM-B150, AMS-4635D	0.875	12	1	2.2
X	C-63200 Rd. Bar TQ50	ASTM-B-150-86	1.25	10	1	3.8
X	C-62400 Rd. Bar HR50	ASTM-B-150	1	116	1	28.2
X	C-62400 Rd. Bar HR50	ASTM-B-150	1.5	22.875	1	12.5
X	C-62400 Rd. Bar HR50	ASTM-B-150	1.75	101	1	75.2
X	C-62400 Rd. Bar HR50	ASTM-B-150	2.5	12.25	1	18.6

X	C-63000 RD BAR	QQC-465B	1.1875	30.125	2	18.5
X	C-63000 RD BAR	QQC-465B	1.1875	92.5	1	29.4
	630 Rd. Bar		1.25	8	1	2.9
X	630 Rd Bar	ASTM-B-150-03	2.25	6	1	7.2
	630 Rd. Bar	QQC-465	2.5	23.375	1	34.4
X	2di/c63000 ni alum brz	ASTM-B150	5.25	24	1	155.7
	63200 Rd. Bar	QQB-465 AM-1 AMPCO 483	0.75	72.5	1	9.6
X	63200 Rd BAR CON-TQ50	ASTM-B-150-03	8.625	3	1	52.5
X	63200 Rd BAR CON-TQ50	ASTM-B-150-03	8.625	3.25	1	56.9
X	C642 Rd. Bar		0.625	72	3	19.9
X	C642 Rd. Bar		0.75	127.125	2	33.7
	C67300 RD BAR	ASTM-B249-06	1	72	1	18.3
X	C67300 RD BAR		1.625	71.75	1	46
X	C67300 RD BAR	ASTM-B249-06	1.625	57.625	1	37
	67300 Rd. Bar		1.625	65	1	40.4
X	CDA 673 RD BAR	ASTM-B249-06	2"	144	1	140
	C67500 Rd. Bar	1/2 Hard	0.625	139.375	1	12.8
X	C65500	ASTM B249	2	5.125	1	4.8
	C71500 Rd. Bar	70/30 CU-NI MIL-C-15726F AM-1 Ann	0.25	59	1	1
	C71500 Rd. Bar	70/30 CU-NI MIL-C-15726F AM-1 Ann	0.75	74	1	10
	C71500 Rd. Bar	70/30 CU-NI MIL-C-15726F AM-1 Temper H01	0.75	71.5	1	9.5
	C71500 Rd.Bar	70/30 CU-NI MIL-C-15726F AM-1 Ann	0.875	11.5	1	2.1
	C71500 Rd. Bar	70/30 CU-NI MIL-C-15726F AM-1 Ann	0.625	11	1	1.0

X	C71500 Rd. Bar	70/30 CU-NI MIL-C-15726F AM-1	0.75	108	1	14.3
	C71500 Rd. Bar	70/30 CU-NI MIL-C-15726F AM-1 Ann	1	45.625	1	10.7
	C71500 Rd. Bar	70/30 CU-NI MIL-C-15726F AM-1 Ann	2	24	1	22.6
X	C71500 Rd. Bar	70/30 CU-NI MIL-C-15726F AM-1	4	1.25	1	4.7
	C71500 Rd. Bar	70/30 CU-NI MIL-C-15726F AM-1 Ann	8.25	1.25	2	40.1
X	C71500 Rd. Bar	70/30 CU-NI MIL-C-15726F AM-1 Ann	9	1.488	1	28.4
<hr/>						
	C93200 Rd. Bar	ASTM-B505	1.375	91.875	1	40.9
<hr/>						
	Silicon Bronze Rd. Bar	ASTM-B98/B249	0.625	72	1	6.6
	Silicon Bronze Rd. Bar	ASTM-B98/B249	0.75	72	2	19.1
	Silicon Bronze Rd.HEX Bar	ASTM-B98/B249	0.625	72	1	6.6
<hr/>						
X	Bronze Bar CDA955	ASTM-B50505	1	36	1	8.5