

<b>TUBE</b>	<b>Spec</b>	<b>T</b>	<b>W</b>	<b>Size</b>
C10100 Tubing	ASTM-F68 Temper ASDRWN	0.375	.032w	72
<hr/>				
C122 Tubing	ASTM-B-280	0.125	0.03	600
C122 Tubing COILS	<b>1-coil at 38.5ft / 2-coils at 50ft</b> ASTM-B-280	0.25	0.03	50-FT
C122 Tubing COILS	ASTM-B-280	0.312	0.032	50 FT
C122 Tubing	<b>1-coil at 32.ft / 2-coils at 50ft</b> ASTM-B-280	0.5	0.032	50ft
C122 Tubing	Cond-H, ASTM-B88	0.5	0.035	120
C122 Tubing	Cond-H, ASTM-B88	0.875	0.045	84
C122 Tubing	ASTM-B88	0.875	0.045	23.75
<hr/>				
Copper Tubing	ASTM-B88	0.625	0.04	35.5
Copper Water Tubing	ASTM-B88	1.125	0.065	25.5
<hr/>				
715 Tube	70/30 Cu-Ni	0.84	0.135	35.875
715 Tube	70/30 Cu-Ni	2.875	0.25	29
<hr/>				
CDA 954 Tube ( 2.3125"od )	ASTM-B505-09	2.5 od	.5 wall	12
<hr/>				