

Bar

	Monel 400 Rd. Bar	Ann. & Pickld, Mil-T-1368C, AM-4	0.312	60.375	4	6.0
	Monel 400 Rd. Bar	QQN-281 CL-A	0.375	119.25	1	4.3
X	MONEL 400 RD BAR	QQ-N-281 D	0.625	67.875	8	47.9
X	Monel 400 Rd. Bar	AMS-4675B, QQN-281D AM2	0.625	71.125	1	7.1
	Monel 400 Rd. Bar	QQN-281 CL-A	1.25	26.75	1	10.7
	Monel 400 Rd. Bar	QQN-281D AM 2, HF, CG	3.25	3.625	1	9.8
	Monel 400 Rd. Bar	QQN-281 CL-A FM-1	4	4.125	1	16.8
	Monel 400 Rd. Bar	QQN-281D, HF	5	6	1	38.3
						140.8

	Monel K500 Rd. Bar	AMS-4676D, QQ-N-286E, HF	1.125	9.25	1	3.0
	Monel K500 Rd. Bar	Ann. & Aged QQN- 286E	1.25	13.875	2	11.1
	Monel 500 Rd. Bar	Hot Finished, age hard Rev-F	1.5	7.375	1	4.2
	Monel K500 Rd. Bar	QQN-286F HF & AGE HARD	1.75	11.5	1	9.0
	Monel K500 Rd. Bar	Ann. QQN-286	2	48	1	49.0
	Monel K500 Rd. Bar	QQN-286 Form 2, Sol Aged	3	72.25	1	165.9
	Monel K500 Rd. Bar	QQN-286F HF, Ann. & Aged	6	9	4	330.7
						572.9

	NI. 200 Rd. Bar	ASTM-B-160	0.188	47.75	1	0.4
	NI. 200 Rd. Bar		0.25	72	2	2.3
	NI. 200 Rd. Bar		0.5	120	1	7.7
X	NI. 200 Rd. Bar	ASTM-B-160	0.75	11.75	1	1.7

	NI. 400 Rd. Bar		0.375		1	0.0
	NI. 400 Rd. Bar	QQN-281 CL-A	0.75	71.5	2	20.5
X	NI 400 RD BAR	QQN-281D AM-2	0.625	31.25	1	2.7
	NI. 400 Rd. Bar		1	152	2	77.6
	NI. 400 Rd. Bar	ASTM-B-164	1.25	27	1	10.8
	NI. 400 Rd. Bar	QQN-281D AM-2	1.5	12	1	6.9
X	NI. 400 Rd. Bar	ASTM-B-164	1.75	33.25	1	118.5

X	HT 600 Wire rod	MIL-N-6710	0.119	45.875	1	0.2
X	NI. 600 Rd. Bar	AMS-5665, Annealed	0.188	53.5	1	0.5
	NI. 600 Rd. Bar	Ann. ASTM-B166	0.187	47.625	1	0.4
	NI. 600 Rd. Bar	AMS-5665	0.25	72	1	1.1
	NI. 600 Rd. Bar	AMS-5665	0.312	26	1	0.6
	NI. 600 Rd. Bar	AMS-5665	0.75	11.875	1	1.7

X	NI. 600 Rd. Bar	AMS-5665	2	7	1	7.1
	NI. 600 Rd. Bar	AMS-5665	5	3.125	1	19.9
						31.5
	NI. 600 Flat Bar		0.25		0	0.0
	NI. 600 Flat Bar		0.25		0	0.0
X	NI. 600 Flat Bar	AMS-5540L	0.562		0	0.0
X	L605 WIRE	AMS-5796E	0.062	36	26	0.8
	L605 Rd. Bar		1.062	20.25	1	5.8
X	625 wire	AWS-514	0.035	36	224	2.5
	Inco 625 Rd. Bar		0.125	118	1	0.5
	Inco 625 Rd. Bar		0.375	16	1	0.6
	Inco 625 Rd. Bar		0.375	6	1	0.2
	Inco 625 Rd. Bar		0.375	29.75	1	1.1
	Inco 625 Rd. Bar		0.5	5	1	0.3
	Inco 625 Rd. Bar	AMS-5666	0.625	22	1	2.2
X	625 Ann Nickel	ASTM-B-446	0.5	34.75	1	2.2
X	625 Ann Nickel	ASTM-B-446	1.01	23.5	1	6.1
						13.2
	Inco 718 Rd. Bar		0.078	36	6	0.3
	Inco 718 Rd. Bar	AMS-5662	0.177	72	2	1.2
	Inco 718 Rd. Bar	AMS-5662	0.215	34.5	2	0.8
X	Inco 718 Rd. Bar	AMS-5662 Cond A	0.25	71.75	1	1.1
	Inco 718 Rd. Bar	AMS-5662 Ann.	0.5	11.25	2	1.4
X	Inco 718 Rd. Bar	AMS-5662	0.5	35.75	2	4.6
	Inco 718 Rd. Bar	AMS-5663 ASTM-B637	0.5	78.25	1	5.0
	Inco 718 Rd. Bar	AMS-5664	0.5	21.125	1	1.3
	Inco 718 Rd. Bar	HT treated to AMS-5664	0.5	68.375	1	4.4
X	Inco 718 Rd. Bar	AMS-5663 ASTM-B637	0.885	79	1	15.8
X	Inco 718 Rd. Bar	AMS-5663 ASTM-B637	0.885	18.75	1	3.7
X	Inco 718 Rd. Bar	AMS-5662	1.125	12.75	1	4.1
	Inco 718 Rd. Bar		1.5	3.75	1	2.2
X	Inco 718 Rd. Bar	AMS-5662, Cond-A, Cond-D	2	7.75	1	7.9
	Inco 718 Rd. Bar	Cond-A, AMS-5662, ASTM-B637	2.5	6.125	1	9.8
X	Inco 718 Rd. Bar	ASTM-A604-93	3.5	0.75	5	11.7
	Inco 718 Rd. Bar	AMS-5664	4	4	1	16.3
X	Inco 718 Rd. Bar	ASTM-A604-93	4	0.75	3	9.2
X	Inco 718 Rd. Bar	AMS-5662	0.25	21.875	1	0.3
	Inco 718 Rd. Bar	Annealed ASTM-6	6	12	1	110.2
						211.4

