

Bar

X	CP Garde 4 Titanium RD BAR	ASTM-B-348 MIL-T-9047	0.375	72	1	1.3
X	CP Titanium Rd. Bar	ASTM-F67-00, Grade 2	0.15	144	2	0.8
	CP Flat bar	Mil-T-9046 (type 13)	0.5	7.875	1	0.3
X	3AL-2.5V Rd. Bar	Annealed, MIL-T-9047	0.5	113.5	2	7.4
	3AL-2.5V Rd. Bar	ASTM-B348	0.5	24.75	1	0.8
	3AL-2.5V Rd. Bar	ASTM-B348	0.5	78.25	4	10.2
	3AL-2.5V Rd. Bar	ASTM-B348	0.531	144	4	21.2
X	6AL-4V ELI RD BAR	AMS-6932	0.5	63.5	1	2
X	6AL-4V Rd. Bar	AMS-4954	0.045	36	610	5.8
X	6AL-4V Rd. Bar	AMS-4954	0.079	36	394	11.5
	6AL-4V Rd. Bar	AMS-4963	0.25	23	1	0.2
X	6AL-4V Rd. Bar	ASTM-B-348	0.25	11.75	1	0.1
	6AL-4V Rd. Bar	AMS-4967TT	0.312	23.875	2	0.6
X	6AL-4V Rd. Bar	Mil-T-9047	0.3125	59.875	1	0.8
X	6AL-4V Rd. Bar	MIL-T-9047	0.315	11.5	1	0.1
X	6AL-4V Rd. Bar	MIL-T-9047	0.322	15	1	0.2
	6AL-4V Rd. Bar	AMS-4928Q	0.375	10	1	0.2
X	6AL-4V Rd. Bar	AMS-4928	0.385	96.875	1	1.8
X	6AL-4V Rd. Bar	AMS-4128	0.437	98.25	1	2.4
X	6AL-4V Rd. Bar	MIL-STD-2154, Class AA	0.563	7	1	0.3
X	6AL-4V Rd. Bar	AMS-4928	0.625	29.5	1	1.5
	6AL-4V Rd. Bar	AMS-4928	0.625	5.625	1	0.3
	6AL-4V Rd. Bar	MIL-T-9047G	1	7.75	1	1.0
X	6AL-4V Rd. Bar	MIL-T-9047 Am2	1	3.75	1	0.5
	6AL-4V Rd. Bar	AMS-4945	1	8.625	1	1.1
X	6AL-4V Rd. Bar	AMS-4965 AMS-4928, MIL-T-9047 Am 2 DMS-1570	1	30	1	3.9
X	6AL-4V RD BAR	MIL-T-9047G	1.375"	72	1	17.5

X	6AL-4V RD BAR	MIL-T-9047G	1.5		6.625	1	1.9
	6AL-4V Rd Bar	MIL-T-9046	2.25		3.75	1	2.5
<hr/>							
	6AL-4V Flat Bar	AMS-4928	0.375	0.875	19.625	1	1.063
X	6AL-4V Bar	ASTM-B348	0.5	1.125	10.375	7	6.741
X	6AL-4V Bar	AMS-4928	0.355	0.59	7.125	1	0.246
	6AL-4V Rect. Bar	AMS-4928N	0.6	0.9	19	1	1.693
	6AL-4V Bar	MIL-T-9046	0.672	0.79	7.25	4	2.54
X	6AL-4V Bar	AMS-T-9046	2	4	4.625	2	12.21
	6AL-4V Bar		2.625	4.75	5.625	1	11.57
<hr/>							
X	TI 13-11-3 ST&A	MIL-T-9047	0.5		72	8	18.8
X	TI 13-11-3 ST&A	MIL-T-9047	0.5		35.5	1	1.2
X	TI 13-11-3 ST&A	MIL-T-9047	0.5		71.75	1	2.3