

## Bar

X	CP Garde 4 Titanium RD BAR	ASTM-B-348 MIL-T-9047	0.375		72	1	1.3
X	CP Titanium Rd. Bar	ASTM-F67-00, Grade 2	0.15		144	2	0.8
	CP Flat bar	Mil-T-9046 (type 13)	0.5		7.875	1	0.3
X	3AL-2.5V Rd. Bar	Annealed, MIL-T-9047	0.5		113.5	2	7.4
	3AL-2.5V Rd. Bar	ASTM-B348	0.5		24.75	1	0.8
	3AL-2.5V Rd. Bar	ASTM-B348	0.5		78.25	4	10.2
	3AL-2.5V Rd. Bar	ASTM-B348	0.531		144	4	21.2
X	6AL-4V Rd. Bar	AMS-4954	0.045		36	610	5.8
X	6AL-4V Rd. Bar	AMS-4954	0.079		36	394	11.5
	6AL-4V Rd. Bar	AMS-4963	0.25		23	1	0.2
X	6AL-4V Rd. Bar	ASTM-B-348	0.25		11.75	1	0.1
	6AL-4V Rd. Bar	AMS-4967TT	0.312		23.875	2	0.6
x	6AL-4V Rd. Bar	Mil-T-9047	0.3125		59.875	1	0.8
X	6AL-4V Rd. Bar	MIL-T-9047	0.315		11.5	1	0.1
X	6AL-4V Rd. Bar	MIL-T-9047	0.322		15	1	0.2
	6AL-4V Rd. Bar	AMS-4928Q	0.375		10	1	0.2
	6AL-4V Rd. Bar	AMS-4128	0.437		62.25	1	1.5
X	6AL-4V Rd. Bar	MIL-STD-2154, Class AA	0.563		7	1	0.3
X	6AL-4V Rd. Bar	AMS-4928	0.625		29.5	1	1.5
	6AL-4V Rd. Bar	AMS-4928	0.625		5.625	1	0.3
X	6AL-4V RD BAR	AMS-4928R	0.635		12	1	0.6
X	6AL-4V Rd. Bar	AMS-4928	0.75		16.875	1	1.2
	6AL-4V Rd. Bar	MIL-T-9047G	1		7.75	1	1.0
X	6AL-4V Rd. Bar	MIL-T-9047 Am2	1		3.75	1	0.5
	6AL-4V Rd. Bar	AMS-4945	1		8.625	1	1.1
		AMS-4965 AMS-4928, MIL-T-9047					
X	6AL-4V Rd. Bar	Am 2 DMS-1570	1		30	1	3.9
X	6AL-4V RD BAR	MIL-T-9047G	1.375"		72	1	17.5
X	6AL-4V RD BAR	MIL-T-9047G	1.5		6.625	1	1.9
	6AL-4V Rd Bar	MIL-T-9046	2.25		3.75	1	2.5
X	6AL-4V Flat Bar	AMS-4928	0.375	0.875	19.625	1	1.063
X	6AL-4V Bar	ASTM-B348	0.5	1.125	10.375	7	6.741
X	6AL-4V Bar	AMS-4928	0.355	0.59	7.125	1	0.246
	6AL-4V Rect. Bar	AMS-4928N	0.6	0.9	19	1	1.693

	6AL-4V Bar		MIL-T-9046	0.672	0.79	7.25	4	2.54
X	6AL-4V Bar		AMS-T-9046	2	4	4.625	2	12.21
X	6AL-4V Bar Consignment		AMS-4928	2.5	2.5	28	6	173.3
	6AL-4V Bar			2.625	4.75	5.625	1	11.57
<hr/>								
X	TI 13-11-3	ST&A	MIL-T-9047	0.5		72	8	18.8
X	TI 13-11-3	ST&A	MIL-T-9047	0.5		35.5	1	1.2
X	TI 13-11-3	ST&A	MIL-T-9047	0.5		71.75	1	2.3